

Section name references in L^AT_EX^{*}

Sebastian Rahtz

2012/07/31

Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

README The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

ChangeLog This file records the version history (also available as text file).

Options This file provides a short option summary.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroTeX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

hyperref.dtx This is the source code documentation for hyperref.

backref.dtx “Back referencing from bibliographical citations”

☞ **nameref.dtx** “Section name references in L^AT_EX” (this file)

Contents

1	Introduction	2
2	History	2
3	Implementation	2
3.1	<code>\label</code> stuff	3
3.2	Changes of section macros	5
3.2.1	Class beamer	7
3.2.2	Theorems	8
3.3	Referencing stuff	8
3.4	Usage and frontend	10
3.5	Package ifthen support	11
3.6	Compatibility with varioref	11
3.7	Support for package listings	13

^{*}This file has version number v2.42, last revised 2012/07/31.

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
 SPQR CERN July 1994;
 Last mod. Sept. 3th MG;
 Sept. 19th SPQR;
 April 11th 1995 SPQR (added section formatting hook);
 April 14th 1995 SPQR (compatibility with hyperref);
 June 22 1995 SPQR (removed typeout from Sectionformat);
 September 22 1997 added varioref hacks by Corey Minyard;
 September 28th changes by David Carlisle.
 More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of `\section`, `\caption`, ...). Then the behaviour switched to expanding, because this allows to remove unwanted macros (`\label`, ...). Despite this method is used in package `titleref` and class `memoir`, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package `getttitlestring` that uses the non-expanding method as default. It also allows me to use this package in package `zref-titleref`. See the package documentation of package `getttitlestring` how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{getttitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

3 Implementation

```
1 \<*package>
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{getttitlestring}[2009/12/18]
4 \RequirePackage{ltxcmds}[2009/12/12]
```

We redefine `\label` so that it also writes the name of the current section to the `.aux` file; if the name ends in a dot, we zap it. To allow for the `hyperref` package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

`\NR@strip@period`

```
5 \def\NR@strip@period#1.\ltx@empty#2\@nil{#1}
```

`\strip@period` Macro `\strip@period` was removed in `nameref` 2012/07/28 v2.41 and reinserted in 2012/07/31 v2.42 for compatibility reasons with package `subfig`.

```
6 \def\strip@period#1.\relax#2\@@@{#1}
```

```

7 \def\NR@sanitize@labelname{%
8   \@onelevel@sanitize\@currentlabelname
9   \edef\@currentlabelname{%
10    \expandafter\NR@strip@period\@currentlabelname
11    \ltx@empty.\ltx@empty\@nil
12   }%
13 }

```

3.1 \label stuff

Here is tested, whether package showkeys is loaded. But if option final is used, the macros of showkeys are not defined, so we have to check an additional test.

\ifNR@showkeys

```

14 \newif\ifNR@showkeys
15 \NR@showkeysfalse
16 \@ifpackageloaded{showkeys}{%
17   \begingroup
18   \@ifundefined{SK@@label}{%
19     }{%
20     \global\NR@showkeystrue
21   }%
22   \endgroup
23 }{}

```

\label@hook

```

24 \providecommand*{\label@hook}{}
25 \ltx@GlobalAppendToMacro{\label@hook}{%
26   \NR@sanitize@labelname
27 }

```

\label

```

28 \def\label#1{%
29   \@bsphack
30   \begingroup
31   \def\label@name{#1}%
32   \label@hook
33   \protected@write\@auxout{}{%
34     \string\newlabel{#1}{%
35       {\@currentlabel}%
36       {\thepage}%
37       {\@currentlabelname}%
38       {\@currentHref}{}%
39     }%
40   }%
41   \endgroup
42   \@esphack
43 }%
44 \ifNR@showkeys
45   \def\label#1{%
46     \@bsphack
47     \SK@\SK@@label{#1}%
48     \begingroup
49     \def\label@name{#1}%
50     \label@hook
51     \protected@write\@auxout{}{%
52       \string\newlabel{#1}{%

```

```

53      {\@currentlabel}%
54      {\thepage}%
55      {\@currentlabelname}%
56      {\@currentHref}{}%
57    }%
58  }%
59  \endgroup
60  \@esphack
61 }%
62 \fi

```

`\ltx@label`

```

63 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

`\slabel`

```

64 \ifundefined{slabel}{%
65   \def\slabel#1{%
66     \@bsphack
67     \if@filesw
68       \begingroup
69       \def\label@name{#1}%
70       \label@hook
71       \let\thepage\relax
72       \def\protect{\noexpand\noexpand\noexpand}%
73       \edef\@tempa{%
74         \write\@auxout{%
75           \string\newlabel{#1}{%
76             {\thesubequation}%
77             {\thepage}%
78             {\@currentlabelname}%
79             {\@currentHref}{}%
80           }%
81         }%
82       }%
83       \expandafter\endgroup
84       \@tempa
85       \if@nobreak\ifvmode\nobreak\fi\fi
86     \fi
87     \@esphack
88   }%
89 }

```

Overload an AMS L^AT_EX command, which uses `\newlabel`. Sigh!

`\@writetocindents@`

```

90 \def\@writetocindents@{%
91   \begingroup
92   \@for\@tempa:=-1,0,1,2,3\do{%
93     \immediate\write\@auxout{%
94       \string\newlabel{tocindent\@tempa}{%
95         \csname r@tocindent\@tempa\endcsname}{-}{-}{-}%
96       }%
97     }%
98   }%
99   \endgroup
100 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

`\NR@gettitle`

```
101 \def\NR@gettitle#1{%
102   \GetTitleString{#1}%
103   \let\@currentlabelname\GetTitleStringResult
104 }
```

First the numbered sections. While we are about it, put in a useful section formatting macro.

`\NR@sect`

```
105 \let\NR@sect\@sect
106 \newcounter{section@level}
```

`\@sect`

```
107 \def\@sect#1#2#3#4#5#6[#7]#8{%
108   \setcounter{section@level}{#2}%
109   \NR@gettitle{#7}%
110   \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[#7]{\Sectionformat{#8}{#2}}%
111 }
```

and now the unnumbered ones

`\NR@ssect`

```
112 \let\NR@ssect\@ssect
```

`\NR@ssect`

```
113 \def\@ssect#1#2#3#4#5{%
114   \NR@gettitle{#5}%
115   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
116 }
```

Support for class memoir.

```
117 \ltx@ifundefined{ifheadnameref}{%
118 }{%
119   \ltx@ifundefined{M@sect}{%
120   }{%
121     \let\NRorg@M@sect\M@sect
122     \def\M@sect#1#2#3#4#5#6[#7][#8]{%
123       \ifheadnameref
124         \NR@gettitle{#8}%
125       \else
126         \NR@gettitle{#7}%
127       \fi
128       \NRorg@M@sect{#1}{#2}{#3}{#4}{#5}{#6}[#7][#8]%
129     }%
130   }%
131 }
```

Parts and chapters are treated differently. sigh. `\@part` and `\@spart` are `\long` because of class memoir.

```

132 \let\NR@part\@part
133 \long\def\@part[#1]#2{%
134   \NR@gettitle{#1}%
135   \NR@part[{#1}]{#2}%
136 }
137 \let\NR@spart\@spart
138 \long\def\@spart#1{%
139   \NR@gettitle{#1}%
140   \NR@spart{#1}%
141 }
142 \let\NR@chapter\@chapter
143 \def\@chapter[#1]#2{%
144   \NR@gettitle{#1}%
145   \NR@chapter[{#1}]{#2}%
146 }
147 \ifclassloaded{memoir}{%
148   \ltx@ifundefined{ifheadnameref}{%
149     {%
150       \def\@chapter[#1]#2{%
151         \ltx@ifundefined{ch@pt@c}{%
152           \NR@gettitle{#1}%
153         }{%
154           \ifx\ch@pt@c\ltx@empty
155             \NR@gettitle{#2}%
156           \else
157             \def\NR@temp{#1}%
158             \ifx\NR@temp\ltx@empty
159               \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
160             \else
161               \ifheadnameref
162                 \NR@gettitle{#1}%
163               \else
164                 \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
165             \fi
166           \fi
167         \fi
168       }%
169       \NR@chapter[{#1}]{#2}%
170     }%
171   }%
172 }{}
173 \let\NR@schapter\@schapter
174 \def\@schapter#1{%
175   \NR@gettitle{#1}%
176   \NR@schapter{#1}%
177 }

```

Captions

```

178 \AtBeginDocument{%
179   \ifpackageloaded{hyperref}{%
180     \ifpackagelater{hyperref}{2009/12/05}\@gobble\@firstofone
181   }\@firstofone
182   {%
183     \let\NR@@caption\@caption
184     \long\def\@caption#1[#2]{%

```

```

185 \NR@gettitle{#2}%
186 \NR@@caption{#1}{#2}%
187 }%
188 }%

189 \ifpackageloaded{longtable}{%
190 \let\NRorg@LT@c@ption\LT@c@ption
191 \def\LT@c@ption#1[#2]#3{%
192 \NRorg@LT@c@ption{#1}{#2}{#3}%
193 \def\@tempa{#2}%
194 \ifx\@tempa\@empty
195 \else
196 \NR@gettitle{#2}%
197 \fi
198 }%
199 }{}%

Environment ‘description’.
200 \ltx@ifundefined{descriptionlabel}{%
201 }{%
202 \let\NRorg@descriptionlabel\descriptionlabel
203 \def\descriptionlabel#1{%
204 \NR@gettitle{#1}%
205 \NRorg@descriptionlabel{#1}%
206 }%
207 }%
208 }

Compatibility for package titlesec.
209 \AtBeginDocument{%
210 \ifpackageloaded{titlesec}{%
211 \let\NRorg@ttl@sect@i\ttl@sect@i
212 \def\ttl@sect@i#1#2[#3]#4{%
213 \NR@gettitle{#4}%
214 \NRorg@ttl@sect@i{#1}{#2}{#3}{#4}%
215 }%
216 }{}%
217 }

```

3.2.1 Class beamer

```

218 \ifclassloaded{beamer}{%
219 \def\NR@PatchBeamer#1{%
220 \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
221 \csname beamer@#1\endcsname
222 \begingroup
223 \edef\x{\endgroup
224 \long\def\expandafter\noexpand\csname beamer@#1\endcsname
225 [####1]{% hash-ok
226 \noexpand\NR@gettitle{####1}%
227 \expandafter\noexpand\csname NRorg@beamer@#1\endcsname
228 [{####1]}%
229 }%
230 }%
231 \x
232 }%
233 \NR@PatchBeamer{section}%
234 \NR@PatchBeamer{subsection}%
235 \NR@PatchBeamer{subsubsection}%

```

236 }{}

3.2.2 Theorems

```
237 \ltx@ifundefined{@opargbegintheorem}{}{%
238   \let\NRorg@opargbegintheorem\@opargbegintheorem
239   \def\@opargbegintheorem#1#2#3{%
240     \NR@getttitle{#3}%
241     \NRorg@opargbegintheorem{#1}{#2}{#3}%
242   }%
243 }
244 \AtBeginDocument{%
245   \ifpackageloaded{amsthm}{%
246     \let\NRorg@begintheorem\@begintheorem
247     \begingroup
248     \edef\x{\macro:\string#1\string#2[\string#3]}%
249     \@onelevel@sanitize\x
250     \def\y#1->#2\@nil{#1}%
251     \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
252     \@onelevel@sanitize\z
253     \expandafter\endgroup
254     \ifx\x\z
255       \def\@begintheorem#1#2[#3]{%
256         \NR@getttitle{#3}%
257         \NRorg@begintheorem{#1}{#2}[#3]}%
258     }%
259   \fi
260 }{ }%
261 }
```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```
262 \providecommand*{\@currentlabelname}{}
263 \providecommand*{\@currentHref}{}%
```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```
\@firstoffive
264 \long\def\@firstoffive#1#2#3#4#5{#1}

\@secondoffive
265 \long\def\@secondoffive#1#2#3#4#5{#2}

\@thirdoffive
266 \long\def\@thirdoffive#1#2#3#4#5{#3}

\@fourthoffive
267 \long\def\@fourthoffive#1#2#3#4#5{#4}

\@offive
268 \long\def\@fifthoffive#1#2#3#4#5{#5}
```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.


```

\@safe@activetrue
269 \providecommand*\@safe@activetrue{}%

\@safe@activesfalse
270 \providecommand*\@safe@activesfalse{}%

\NR@setref
271 \def\NR@setref#1{%
272   \begingroup
273   \@safe@activetrue
274   \expandafter
275   \endgroup
276   \expandafter\NR@@setref\csname r@#1\endcsname
277 }

\NR@@setref
278 \def\NR@@setref#1{%
279   \ifx\@undefined#1%
280     \let#1\relax
281   \fi
282   \@setref#1%
283 }

\T@ref
284 \def\T@ref#1{%
285   \NR@setref{#1}\@firstoffive{#1}%
286 }%

\T@pageref
287 \def\T@pageref#1{%
288   \NR@setref{#1}\@secondoffive{#1}%
289 }%

290 \ifNR@showkeys
291   \ifx\SK@ref\@empty
292     \else

\T@ref
293   \def\T@ref#1{%
294     \@safe@activetrue
295     \SK@\SK@@ref{#1}%
296     \@safe@activesfalse
297     \NR@setref{#1}\@firstoffive{#1}%
298   }%

\T@pageref
299   \def\T@pageref#1{%
300     \@safe@activetrue
301     \SK@\SK@@ref{#1}%
302     \@safe@activesfalse
303     \NR@setref{#1}\@secondoffive{#1}%
304   }%

305   \fi
306   \fi

```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`. Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```
307 \ifpackageloaded{hyperref}{%
308 }{%
```

`\ref`

```
309 \DeclareRobustCommand{\ref}{\T@ref}%
```

`\pageref`

```
310 \DeclareRobustCommand{\pageref}{\T@pageref}%
```

```
311 }
```

3.4 Usage and frontend

Access the (third) name part with `\nameref`;

`\T@nameref`

```
312 \def\T@nameref#1{%
313 \begingroup
314 \let\label\@gobble
315 \NR@setref{#1}\@thirdoffive{#1}%
316 \endgroup
317 }%
318 \ifNR@showkeys
319 \ifx\SK@ref\@empty
320 \else
321 \def\T@nameref#1{%
322 \@safe@activestrue
323 \SK@\SK@@ref{#1}%
324 \@safe@activesfalse
325 \begingroup
326 \let\label\@gobble
327 \NR@setref{#1}\@thirdoffive{#1}%
328 \endgroup
329 }%
330 \fi
331 \fi

332 %\@ifclassloaded{memoir}{%
333 % \ltx@ifundefined{@mem@titlerefno link}\ltx@secondoftwo{%
334 % \ltx@ifundefined{@mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
335 % }%
336 %}\ltx@secondoftwo
337 %}%
338 % \DeclareRobustCommand*{\nameref}{%
339 % \@ifstar\@mem@titlerefno link\@mem@titleref
340 % }%
341 %}{%}
```

`\nameref`

```
342 \DeclareRobustCommand*{\nameref}{%
343 \@ifstar\T@nameref\T@nameref
344 }%
345 %}
```

`\Nameref` An extended form which gives title and page number.
346 `\def\Nameref#1{'\nameref{#1}' on page~\pageref{#1}}`

`\Sectionformat` The default for `\Sectionformat`
347 `\providecommand\Sectionformat[2]{#1}`

3.5 Package ifthen support

Package ifthen's `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```

348 \@ifpackageloaded{ifthen}{%
349   \let\NROrg@ifthenelse\ifthenelse
350   \def\ifthenelse{%
351     \let\begingroup\NR@TE@begingroup
352     \NROrg@ifthenelse
353   }%
354   \let\NROrg@begingroup\begingroup
355   \def\NR@TE@begingroup{%
356     \let\begingroup\NROrg@begingroup
357     \begingroup
358     \def\ref##1{\getrefbykeydefault{##1}{}{??}}%
359     \def\pageref##1{\getrefbykeydefault{##1}{page}{0}}%
360   }%
361 }{}
```

3.6 Compatibility with varioref

[This section was derived by Corey Minyard minyard@acm.org from the `varioref` package]

```

362 \AtBeginDocument{%
363   \ifx\csname @@vpageref\endcsname\relax
364   \else
365     \def\@@vpageref#1[#2]#3{%
366       \begingroup
367       \csname @safe@activetrue\endcsname
368       \edef\x{#3}%
369       \@onelevel@sanitize\x
370       \toks@{%
371         \NR@@vpageref{#1}{#2}}%
372       }%
373       \edef\x{\endgroup
374         \the\toks@{\x}}%
375       }%
376       \x
377     }%
378     \def\NR@@vpageref#1[#2]#3{%
379       \leavevmode\unskip
380       \global\advance\c@vrcnt\@ne
381       \ifundefined{r@the\c@vrcnt@vr}%
382       {\@namedef{r@the\c@vrcnt@vr}{??}{??}{}}{}%
383       \edef\@tempa{%
384         \expandafter\expandafter\expandafter
385         \@secondoffive\csname r@the\c@vrcnt@vr\endcsname
```

```

386 }%
387 \@ifundefined{r@\the\c@vrcnt @xvr}%
388   {\@namedef{r@\the\c@vrcnt @xvr}{\{??\}{??\}{\}{\}}}%
389 \edef\@tempb{%
390   \expandafter\expandafter\expandafter
391   \@secondoffive\csname r@\the\c@vrcnt @xvr\endcsname
392 }%
393 {%
394   \let\@currentlabel\@empty
395   \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
396 }%
397 \ifx\@tempa\@tempb
398 \else
399   \vref@err{%
400     \noexpand\vref at page boundary %
401     \@tempb-\@tempa\space (may loop)%
402   }%
403 \fi
404 \@ifundefined{r@#3}{\@namedef{r@#3}{\{??\}{??\}{\}{\}}}%
405 \edef\thevpagerefnum{%
406   \expandafter\expandafter\expandafter
407   \@secondoffive\csname r@#3\endcsname
408 }%
409 \ifx\vref@space\@undefined
410   \space
411 \else
412   \vref@space
413 \fi
414 \ifx\@tempa\thevpagerefnum
415   #1%
416 \else
417   #2%
418   \is@pos@number\thevpagerefnum{%
419     \is@pos@number\@tempa{%
420       \@tempcnta\@tempa
421       \advance\@tempcnta\@ne
422     }{%
423       \@tempcnta\maxdimen
424     }%
425     \ifnum \thevpagerefnum =\@tempcnta
426       \ifodd\@tempcnta
427         \if@twoside
428           \reftextfaceafter
429         \else
430           \reftextafter
431         \fi
432       \else
433         \reftextafter
434       \fi
435     \else
436       \advance\@tempcnta-2 %
437       \ifnum \thevpagerefnum =\@tempcnta
438         \ifodd\@tempcnta
439           \reftextbefore
440         \else
441           \if@twoside
442             \reftextfacebefore

```

```

443         \else
444         \reftextbefore
445         \fi
446     \fi
447     \else
448     \reftextfaraway{#3}%
449     \fi
450     \fi
451 }{%
452     \reftextfaraway{#3}%
453 }%
454 \fi
455 {%
456     \let\@currentlabel\@empty
457     \expandafter\label\expandafter{\the\c@vrcnt \@vr}%
458 }%
459 }%
460 \DeclareRobustCommand\vnameref[1]{%
461     \unskip~\nameref{#1}%
462     \@vpageref[\unskip]{#1}%
463 }%
464 \fi
465 }

466 \ifundefined{@Refstar}{%
467     \def\T@Ref#1{%
468         \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
469     }%
470     \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
471         \MakeUppercase#1%
472     }%
473 }{}%
474 \AtBeginDocument{%
475     \ifpackageloaded{varioref}{%
476         \ifundefined{@Refstar}{%
477             \DeclareRobustCommand*\Ref}[1]{%
478                 \T@Ref{#1}%
479             }%
480         }{}%
481     }{}%
482 }%

```

3.7 Support for package listings

```

483 \AtBeginDocument{%
484     \ifpackageloaded{listings}{%
485         \let\NR@Org@lst@MakeCaption\lst@MakeCaption
486         \def\lst@MakeCaption{%
487             \ifx\lst@label\@empty
488             \else
489                 \let\@currentlabelname\lst@@caption
490             \fi
491             \NR@Org@lst@MakeCaption
492         }%
493     }{}%
494 }

495 \end{package}

```

4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\@@@ 6	\@safe@activetrue 269,	\def 5, 6,
\@vpageref 365	273, 294, 300, 322	7, 28, 31, 45, 49,
\@auxout . . 33, 51, 74, 93	\@schapter 173, 174	65, 69, 72, 90,
\@begintheorem	\@secondoffive	101, 107, 113,
. 246, 251, 255 265, 288,	122, 133, 138,
\@bsphack 29, 46, 66	303, 385, 391, 407	143, 150, 157,
\@caption 183, 184	\@sect 105, 107	174, 184, 191,
\@chapter . . 142, 143, 150	\@setref 282	193, 203, 212,
\@currentHref	\@spart 137, 138	219, 224, 239,
. 38, 56, 79, 263	\@sssect 112, 113	250, 255, 264,
\@currentlabel	\@tempa 73, 84,	265, 266, 267,
. 35, 53, 394, 456	92, 94, 95, 193,	268, 271, 278,
\@currentlabelname	194, 383, 397,	284, 287, 293,
. 8, 9, 10, 37,	401, 414, 419, 420	299, 312, 321,
55, 78, 103, 262, 489	\@tempb . . 389, 397, 401	346, 350, 355,
\@empty . . 194, 291,	\@tempcnta 420,	358, 359, 365,
319, 394, 456, 487	421, 423, 425,	378, 467, 470, 486
\@esphack 42, 60, 87	426, 436, 437, 438	\@descriptionlabel 202, 203
\@fifthoffive 268	\@thirdoffive 266, 315, 327	\do 92
\@firstoffive 264, 285, 297	\@undefined . . . 279, 409	
\@firstofone . . . 180, 181	\@vpageref 462	E
\@for 92	\@writetocindents@ . . 90	\edef 9, 73, 223,
\@fourthoffive 267		248, 251, 368,
\@gobble . . 180, 314, 326	A	373, 383, 389, 405
\@ifclassloaded	\advance . . 380, 421, 436	\else 125, 156,
. 147, 218, 332	\AtBeginDocument 178, 209,	160, 163, 195,
\@ifpackagelater . . . 180	244, 362, 474, 483	292, 320, 364,
\@ifpackageloaded		398, 411, 416,
. 16, 179,	B	429, 432, 435,
189, 210, 245,	\begingroup 17,	440, 443, 447, 488
307, 348, 475, 484	30, 48, 68, 91,	\endcsname 95,
\@ifstar 339, 343	222, 247, 272,	220, 221, 224,
\@ifundefined	313, 325, 351,	227, 276, 363,
. 18, 64, 381,	354, 356, 357, 366	367, 385, 391, 407
387, 404, 466, 476		\endgroup 22, 41, 59,
\@mem@titleref 339	C	83, 99, 223, 253,
\@mem@titlerefnoLink 339	\c@vrcnt . . 380, 381,	275, 316, 328, 373
\@namedef . . 382, 388, 404	382, 385, 387,	\expandafter
\@ne 380, 421	388, 391, 395, 457 10, 83, 159,
\@nil 5, 11, 250, 251	\ch@pt@c . . 154, 159, 164	164, 220, 224,
\@offive 268	\csname 95,	227, 251, 253,
\@onelevel@sanitize	220, 221, 224,	274, 276, 384,
. 8, 249, 252, 369	227, 276, 363,	390, 395, 406, 457
\@opargbegintheorem	367, 385, 391, 407	F
. 238, 239		\fi 62, 85, 86,
\@part 132, 133	D	127, 165, 166,
\@safe@activesfalse	\DeclareRobustCom-	167, 197, 259,
. 270, 296, 302, 324	mand 309, 310,	281, 305, 306,
	338, 342, 460, 477	330, 331, 403,
		413, 431, 434,

445, 446, 449, 450, 454, 464, 490	\ltx@label 63	\NROrg@ifthenelse 349, 352
	\ltx@secondoftwo 333, 334, 336	\NROrg@lst@Make- Caption . 485, 491
G	M	\NROrg@LT@cOption 190, 192
\getrefbykeydefault 358, 359	\M@sect 121, 122	\NROrg@M@sect 121, 128
\GetTitleString 102	\MakeUppercase ... 471	\NROrg@opargbe- gintheorem 238, 241
\GetTitleStringResult 103	\maxdimen 423	\NROrg@ttl@sect@i 211, 214
\global 20, 380	\meaning 251	
I	N	P
\if@filesw 67	\Nameref 346	\pageref ... 310, 346, 359
\if@nobreak 85	\nameref 338, 342, 346, 461	\protect 72
\if@twoside ... 427, 441	\newcounter 106	\protected@write . 33, 51
\ifheadnameref 123, 161	\newif 14	\providecommand 24, 262, 263, 269, 270, 347
\ifNR@showkeys 14, 44, 290, 318	\newlabel . 34, 52, 75, 94	
\ifnum 425, 437	\nobreak 85	R
\ifodd 426, 438	\noexpand 72, 224, 226, 227, 400	\Ref 477
\ifthenelse 349, 350	\NR@@caption . 183, 186	\ref 309, 358
\ifvmode 85	\NR@@setref .. 276, 278	\reftextafter .. 430, 433
\ifx 154, 158, 194, 254, 279, 291, 319, 363, 397, 409, 414, 487	\NR@@vpageref 371, 378	\reftextbefore . 439, 444
\immediate 93	\NR@chapter 142, 145, 169	\reftextfaceafter 428
\is@pos@number 418, 419	\NR@gettitle 101, 109, 114, 124, 126, 134, 139, 144, 152, 155, 159, 162, 164, 175, 185, 196, 204, 213, 226, 240, 256	\reftextfacebefore .. 442
L	\NR@MakeUppercase- FirstOfFive 468, 470	\reftextfaraway 448, 452
\label 28, 63, 314, 326, 395, 457	\NR@part 132, 135	\relax ... 6, 71, 280, 363
\label@hook 24, 32, 50, 70	\NR@PatchBeamer . .. 219, 233, 234, 235	\RequirePackage . 2, 3, 4
\label@name . 31, 49, 69	\NR@sanitize@label- name 7, 26	S
\leavevmode 379	\NR@schapter . 173, 176	\Sectionformat 110, 115, 347
\let 63, 71, 103, 105, 112, 121, 132, 137, 142, 173, 183, 190, 202, 211, 220, 238, 246, 280, 314, 326, 349, 351, 354, 356, 394, 456, 485, 489	\NR@sect 105, 110	\setcounter 108
\long 133, 138, 184, 224, 264, 265, 266, 267, 268	\NR@setref 271, 285, 288, 297, 303, 315, 327, 468	\SK@ .. 47, 295, 301, 323
\lst@@caption 489	\NR@showkeysfalse .. 15	\SK@@label 47
\lst@label 487	\NR@showkeystrue .. 20	\SK@@ref . 295, 301, 323
\lst@MakeCaption 485, 486	\NR@spart ... 137, 140	\SK@ref 291, 319
\LT@cOption .. 190, 191	\NR@ssect 112, 113	\slabel 64
\ltx@empty 5, 11, 154, 158	\NR@strip@period . 5, 10	\space 401, 410
\ltx@firstoftwo 334	\NR@TE@begingroup 351, 355	\string 34, 52, 75, 94, 248
\ltx@GlobalAppend- ToMacro 25	\NR@temp ... 157, 158	\strip@period 6
\ltx@ifUndefined 117, 119, 148, 151, 200, 237, 333, 334	\NROrg@begingroup 354, 356	T
	\NROrg@begintheorem 246, 257	\T@nameref ... 312, 343
	\NROrg@descriptionla- bel 202, 205	\T@pageref 287, 299, 310
		\T@Ref 467, 478
		\T@ref 284, 293, 309
		\the 374, 381, 382, 385, 387, 388, 391, 395, 457
		\thepage .. 36, 54, 71, 77
		\thesubequation 76
		\thevpagerefnum 405, 414, 418, 425, 437
		\toks@ 370, 374

\ttl@sect@i . . .	211, 212	\vref@err	399	249, 254, 368,
		\vref@space . . .	409, 412	369, 373, 374, 376
U				
\unskip . . .	379, 461, 462	W		
		Y		
V		\write	74, 93	\y 250, 251
\vnameref	460	X		
\vref	400	\x	223, 231, 248,	\z 251, 252, 254
		Z		